



- NILE
SERIES
- PUSUNG
SERIES
- DIY KIT
SERIES
- POLO
SERIES
- RV POWER
SUPPLY
SERIES
- SMALL HIGH
VOLTAGEHOME
SERIES
- INDUSTRUAL AND
COMMERCIAL
SERIES

INDUSTRUAL AND
COMMERCIALSERIES

220KWH



Technical Parameters

PRODUCT PERFORMANCE	HVS-R215P100-M
DC SIDE VOLTAGE RANGE	594V-792V
OUTPUT VOLTAGE	380V@AC
SYSTEM CONFIGURATION	1P220S
RATED POWER	100KW
MATCHING PCS	100KW
NOMINAL ENERGY OF BATTERY SYSTEM	215KWH
BATTERY UPLOAD REQUEST VALUE	5%-95%
BATTERY PROTECTION VALUE	2.7V-3.6V
DISCHARGEABLE ENERGY	≥193.5KWH
BATTERY CYCLE EFFICIENCY	≥90%@AC
SIZE(L*W*H)	2250*1050*2360mm
WEIGHT	2500KG
IP RATING	IP55
OPERATING TEMPERATURE RANGE	-20-50℃
OPERATING HUMIDITY RANGE	≤95%(NO CONDENSATION)
BATTERY TEMPERATURE CONTROL METHOD	AIR COOLING
FIRE PROTECTION SYSTEM	AEROSOL

