



- NILE  
SERIES
- PUSUNG  
SERIES
- DIY KIT  
SERIES
- POLO  
SERIES
- RV POWER  
SUPPLY  
SERIES
- SMALL HIGH  
VOLTAGEHOME  
SERIES
- INDUSTRUAL AND  
COMMERCIAL  
SERIES

INDUSTRUAL AND  
COMMERCIALSERIES  
HITEN-104



- Rapid maintenance
- Aerosol firefighting
- Forced air cooling



Technical Parameters

| PRODUCT PERFORMANCE                | HV25-HITEN-104 | HV50HITEN-104  |
|------------------------------------|----------------|----------------|
| RATED LOAD                         | 26.64KWH       | 53.2KWH        |
| CONFIGURATION                      | 5*1P16S        | 10*16S1P       |
| RATED VOLTAGE                      | 256V           | 512V           |
| RATED CAPACITY                     | 104AH          | 104AH          |
| OPERATING VOLTAGE RANGE            | 216-292V       | 432-584V       |
| RATED CHARGE AND DISCHARGE CURRENT | 100A           | 100A           |
| RATED CHARGE AND DISCHARGE POWER   | 26KW           | 51KW           |
| NET WEIGHT                         | 364KG±3KG      | 650KG±6KG      |
| SIZE                               | 860*760*1248mm | 860*760*2077mm |
| GROSS WEIGHT                       | 419KG±4KG      | 723KG±7KG      |
| COMMUNICATION                      | CAN/RS485      | CAN/RS485      |
| STORAGE TEMPERATURE                | -10~30°C       | -10~30°C       |
| CHARGING TEMPERATURE               | 0~40°C         | 0~40°C         |
| DISCHARGE TEMPERATURE              | -20~40°C       | -20~40°C       |
| WATERPROOF GRADE                   | IP20           | IP20           |