



- NILE
SERIES
- PUSUNG
SERIES
- DIY KIT
SERIES
- POLO
SERIES
- RV POWER
SUPPLY
SERIES
- SMALL HIGH
VOLTAGEHOME
SERIES
- INDUSTRIAL AND
COMMERCIAL
SERIES

RV POWER SUPPLY SERIES
FT12-280



Technical Parameters

PRODUCT PERFORMANCE	FT12-280
STANDARD VOLTAGE	12.8V
RATED CAPACITY	280AH
OPERATING VOLTAGE	10.4V-14.4V
STANDARD CHARGING CURRENT	100A
MAXIMUM CHARGE/DISCHARGE CURRENT	200A
OPERATING TEMPERATURE RANGE	0-40°C(CHARGE)-20-40°C(DISCHARGE)
STORAGE TEMPERATURE	-10°C~35°C (1MONTHS) 25±2°C (3MONTHS) 65%±20%RH
CYCLE LIFE	6000 CYCLES @25°C 50A CHARGE AND DISCHARGE CURRENT 70% STANDARD CAPACITY 80% DOD
COMMUNICATION	CAN&RS485
WATERPROOF GRADE	IP20
HUMIDITY RANGE	5~95%
NET SIZE	400*220*260MM
NET WEIGHT	34.2±3KG

