

HITEN-HV-AC-S5



HITEN-HV-AC-S4



HITEN-HV-AC-S3



HITEN-HV-AC-S2







- NILE
SERIES
- PUSUNG
SERIES
- DIY KIT
SERIES
- POLO
SERIES
- RV POWER
SUPPLY
SERIES
- SMALL HIGH
VOLTAGEHOME
SERIES
- INDUSTRIAL AND
COMMERCIAL
SERIES

SMALL HIGH VOLTAGEHOME
SERIES

HITEN-50



Technical Parameters

PRODUCT PERFORMANCE	HV-AC-S2	HV-AC-S3	HV-AC-S4	HV-AC-S5
RATED CAPACITY	10.24 KWH	15.3KWH	20.4 KWH	25.6KWH
CELL TYPE	LITHIUM IRON PHOSPHATE	LITHIUM IRON PHOSPHATE	LITHIUM IRON PHOSPHATE	LITHIUM IRON PHOSPHATE
CELL CONFIGURATION	2*32S1P	3*32S1P	4*32S1P	5*32S1P
RATED VOLTAGE	204.8V	307.2V	409.6V	512V
RATED CAPACITY	50AH	50AH	50AH	50AH
OPERATING VOLTAGE RANGE	172.8V-233.6V	259.2-350.4V	345.6-467.2V	432-584V
RATED CHARGE AND DISCHARGE CURRENT	50A	50A	50A	50A
RATED CHARGE AND DISCHARGE POWER	10.24 KW	15.36 KW	20.48 KW	25.6 KW
COMMUNICATION	CAN/RS485			
CYCLE LIFE	6000			
OPERATING TEMPERATURE RANGE	-15-45°C			
RELATIVE HUMIDITY	5%-65%			
WEIGHT	121±4KG	169±6KG	217±8KG	265±10KG
SIZE (L*W*H)	630*380*720MM	630*380*920MM	630*380*1120MM	630*380*1320MM
BATTERY BOX PACKAGING WEIGHT	64KG			
MAIN CONTROL BOX PACKAGING WEIGHT	24.3KG			

